UNVC

687

The Vertical Cable Manager mounts to a Floor Screen to conceal and route cables from floor to desk height.


Vertical Cable Manager

WHAT'S INCLUDED

Vertical cable manager (back and cover plate), attachment hardware.

NOTES

The North American height is 26". The additional height of 23" is for International requirements and enables an outlet box to be mounted above the cable manager.



PRODUCT OPTIONS

Height	Finish
23, 26	Foundation
	Mica

SAMPLE ORDER CODE

UNVC 26	Q
---------	---

DIMENSIONS INCHES / MM	PRICING	
Н		
23 / 584	178	
26 / 660	198	

ZOEWM

Casual Wire Manager Kit

The Casual Wire Management Kit is applied to District credenzas to conceal and route wiring.

WHAT'S INCLUDED

 $2 \times 24"$ casual wire managers, $4 \times 4"$ casual wire managers.

NOTES

Finished in Ebony.

This product is mounted by double-sided tape and can be trimmed in length.



PRICING

The Data Extender Plate is placed over a communication opening to provide extended depth for data jacks which may be required in some applications. Consult your data cabling supplier for clearance requirements.

UNQDE Data Extender Plate

WHAT'S INCLUDED

1 data extender plate.



PRODUCT OPTIONS

UNQCMP Compatibility Power Harness

The Compatibility Harness is used to connect harnesses from old District electrics to harnesses from the new District electrics. This allows both systems to be used in the same configuration.

WHAT'S INCLUDED

1 harness.



PRODUCT OPTIONS

Wire System	Country of Installation
8T 8-Wire Isolated Ground	A Canada/U.S.A.
8K 8-Wire Dual Isolated	

SAMPLE ORDER CODE

UNQCMP 8K	A
-----------	---

PRICING

145

The Chicago Power Box provides one duplex and one communications opening on either one or both sides of a Panel Wall.

UNQPRCH Chicago Power Box

WHAT'S INCLUDED


Power box, 1 or 2 faceplates (as specified). Internal wiring (3-wire connection).

WHAT'S EXCLUDED

No connector provided.

NOTES

Faceplates have a Platinum painted finish.



PRODUCT OPTIONS

	Application	Mounting Location	Country of Installation
SA	Single Length, One-Sided	L Below Worksurface Height (Base Fascia)	A Canada/U.S.A.
SB	Single Length, Back-to-Back	U Above Worksurface Height (Upper Fascia)	
DA	Double Length, One-Sided		
DB	Double Length, Back-to-Back		

SAMPLE ORDER CODE

UNQPRCH A	U	Α
-----------	---	---

APPLICATION	PRICING
SA	
SB	302
DA	304
DB	353

UNQBFRCH Chicago Base Feed


The Chicago Base Feed delivers power to a Panel Wall at base level and provides entry for data communication feeds.

WHAT'S INCLUDED

Base feed, 72" liquid-tite cable, data/communications bezel mounting hardware. Internal wiring (3-wire connection).

WHAT'S EXCLUDED

No strain relief connector provided.



PRODUCT OPTIONS

Length	Country of Installation	Bezel Finish
72	A Canada/U.S.A.	YY Ebony
		YF Storm White
		YN Platinum Grey Coordinate

SAMPLE ORDER CODE

UNQBFRCH 72	A	YY
-------------	---	----

PRICING

The Chicago Ceiling Feed routes power from the ceiling into Panel Walls.

WHAT'S INCLUDED

Ceiling feed harness, junction box, mounting hardware.

WHAT'S EXCLUDED

Chicago Power Distribution Box (UNQDBCH) must be specified separately.

No strain relief connector provided.





PRODUCT OPTIONS

Length	Country of Installation
120	A Canada/U.S.A.

SAMPLE ORDER CODE

UNQCFRCH 120	A
--------------	---

PRICING

EWWT Under Cabinet Wire Tray

The Under Cabinet Wire Tray manages wires horizontally below the storage cabinet.


WHAT'S INCLUDED

1 wire tray and mounting hardware.

NOTES

Tray ${\bf cannot}$ span across two storage units. Specify at least 12" less than the width of the cabinet onto which it is being mounted.

Finished in Platinum.



PRODUCT OPTIONS

12, 24, 36, 48, 60, 72, 84	

SAMPLE ORDER CODE

EWWT 72

DIMENSIONS INCHES / MM	PRICING		
L			
12 / 305	23		
24 / 610	39		
36 / 914	59		
48 / 1219	76		
60 / 1524	98		
72 / 1829	115		
84 / 2134	131		

Storage Base Feed

EWBF

The Storage Base Feed provides power from the floor to the underside of the storage cabinet and connects to the harness.

WHAT'S INCLUDED

Base feed, 72" liquid-tite cable, I-connector, mounting hardware.

NOTES

Can be directly connected to the Flush Mounted Power & Data (EWQP) unit once I-connector is removed.



PRODUCT OPTIONS

Wire System	Length	Country of Installation	PVC Free
8T 8-Wire Isolated Ground	72, 144	A Canada/U.S.A.	- Standard
8K 8-Wire Dual Isolated			V PVC Free

SAMPLE ORDER CODE

EWBF 8K 72	A	V
------------	---	---

DIMENSIONS INCHES / MM

	8-WIRE DUAL	3-WIRE DUAL ISOLATED (8K)		8-WIRE ISOLATED GROUND (8T)	
L	Standard	PVC Free (V)	Standard	PVC Free (V)	
72 / 1529	220	448	220	448	
144 / 3658	305	646	305	646	

EWBFCH Storage Chicago Base Feed



The Storage Chicago Base Feed delivers power from the floor to the underside of the storage cabinet.

WHAT'S INCLUDED

Base feed, 72" liquid-tite cable, mounting hardware.

NOTES

Storage Chicago Base Feed (EWBFCH) comes with a 3-wire. No connection is provided on the bottom end due to Chicago electrics wiring restrictions.

Chicago electrics wiring restrictions require that all wiring and connections be supplied and connected by a licensed electrician.

PRODUCT OPTIONS

Length	Country of Installation
72	A Canada/U.S.A.
SAMPLE ORDER CODE	

	EWBFCH 72	A
--	-----------	---

PRICING

233

The Storage Split Base Feed delivers power from the floor to the underside of the storage cabinet. It is wired to the building power supply in two places for New York city wiring restrictions.


EWBFS Storage Split Base Feed

WHAT'S INCLUDED

1 base feed harness, junction box, I-connector, mounting hardware.

NOTES

Can be directly connected to the Flush Mounted Power & Data (EWQP) unit once I-connector is removed.



PRODUCT OPTIONS

~ Standard
V PVC Free

SAMPLE ORDER CODE

EWBFS 8K 72	A	V
-------------	---	---

DIMENSIONS INCHES / MM

	8-WIRE DUAL	ISOLATED (8K)	8-WIRE ISOLA	TED GROUND (8T)	
L	Standard	PVC Free (V)	Standard	PVC Free (V)	
18 / 457	277	366	249	333	
72 / 1529	355	599	322	543	

EWCF

Storage Ceiling Feed



The Storage Ceiling Feed routes power to the underside of the storage cabinet from the ceiling through the storage power pole.

WHAT'S INCLUDED

ceiling feed harness, junction box, I-connector, mounting hardware.

NOTES

Can be directly connected to the Flush Mounted Power & Data (EWQP) unit once I-connector is removed.

PRODUCT OPTIONS

Wire System	Length	Country of Installation	PVC Free
8T 8-Wire Isolated Ground	120, 144	A Canada/U.S.A.	- Standard
8K 8-Wire Dual Isolated			V PVC Free

SAMPLE ORDER CODE

EWCF 8K	120	A	V
---------	-----	---	---

DIMENSIONS INCHES / MM

	8-WIRE DUAL ISOLATED (8K)		8-WIRE ISOLA	ATED GROUND (8T)	
L	Standard	PVC Free (V)	Standard	PVC Free (V)	
120 / 3048	344	532	249	333	
144 / 3658	377	487	311	421	

The Storage Chicago Ceiling Feed routes power into the underside of the storage cabinet from the ceiling through the Storage Power Pole (EWEP).

WHAT'S INCLUDED

ceiling feed harness, junction box, mounting hardware.

NOTES

The Storage Chicago Ceiling Feed (EWCFCH) comes with a 3-wire. No connector is found on the bottom end due to Chicago electrics wiring restrictions.

Chicago electrics wiring restrictions require that all wiring and connections be supplied and connected by a licensed electrician.

EWCFCH Storage Chicago Ceiling Feed



PRODUCT OPTIONS

S.A.
,

SAMPLE ORDER CODE

EWCFCH 144 A

DIMENSIONS INCHES / MM	PRICING
L	
120 / 3048	155
144 / 3658	188

EWBH Storage Power Harness

The Storage Power Harness carries power along the base of the cabinet to the Flush Mount Power & Data box or the Cubby Power Monument (EWQPM) in the storage

WHAT'S INCLUDED

1 power harness.

 \mbox{NOTES} The 24" length is all mesh. Other lengths have mesh on both ends for maximum flexibility in a storage application.

To specify the correct length of power harness, determine the distance from the center of one cut out to the other, then add 24".

In order to plug into a Cubby Power Monument (EWQPM), a 4-Way Splitter (EWDB) or an I-Connector (EWIC) must be specified separately.



PRODUCT OPTIONS

Wire System	Length	Country of Installation	PVC Free
8T 8-Wire Isolated Ground	24, 48, 72, 96, 120, 144	A Canada/U.S.A.	- Standard
8K 8-Wire Dual Isolated			V PVC Free

SAMPLE ORDER CODE

EWBH 8K	72	A	V
---------	----	---	---

DIMENSIONS **INCHES / MM**

	8-WIRE DUA	8-WIRE DUAL ISOLATED (8K)		8-WIRE ISOLATED GROUND (8T)	
L	Standard	PVC Free (V)	Standard	PVC Free (V)	
24 / 610	120	149	120	149	
48 / 1219	184	220	184	220	
72 / 1829	207	247	207	247	
96 / 2438	250	300	250	300	
120 / 3048	295	354	295	354	
144 / 3658	337	405	337	405	

The 4-Way Splitter attaches to a harness to split power at floor level.

WHAT'S INCLUDED

1 4-way splitter and hardware.

E W D B 4-Way Splitter



The I-Connector is used to join two harnesses when a single harness length is not long enough.

EWIC I-Connector

WHAT'S INCLUDED

1 I-connector.



PRODUCT OPTIONS

Country of Installation		
A Canada/U.S.A.		
SAMPLE ORDER CODE		
EWIC A		
EWDB 4-WAY SPLITTER	EWIC I-CONNECTOR	
110	34	

EWQP Flush Mount Power & Data

Base Height Beltline Height

The Flush Mount Power & Data is a module that mounts to the back of a case where a drawer is located. This allows for accessibility of power and data from the back side of a storage unit.

WHAT'S INCLUDED

Base Height: 1 power box, faceplate, back cover, mounting hardware.

Beltline Height: 1 power box, faceplate, back cover, mounting hardware, four-way splitter, 1 power harness (to cover vertical distance to base).

WHAT'S EXCLUDED

Receptacle Outlets (EWRO) must be specified separately. Can be found on page 704.

Data and communication must be sourced separately.

NOTES

Flush Mounted Power & Data (EWQP) units can also mount to the back cubby of a Pedestal or Pedestal Tower.

PRODUCT OPTIONS

	Power Location	Wire System	Country of Installation	Bezel Finish	PVC Free
B	Base Height	8T 8-Wire Isolated Ground	A Canada/U.S.A.	YY Ebony	- Standard
E	Beltline Height	8K 8-Wire Dual Isolated		YF Storm White	V PVC Free
				YN Platinum Grey Coordinate	
				YV Very White	

SAMPLE ORDER CODE

EWQP B	8K	A	YF	v
--------	----	---	----	---

POWER LOCATION

PRICING

	Standard	PVC Free (V)	
В	360	433	
Е	500	600	